## **SIEMENS**

Product data sheet 5SM1342-0



RES.CURRENT OP.CIRCUIT BREAKER TYPE AC WS D=55MM 25A 3+N-POL IFN 30MA 400V 4MW

Similar to image

Technical data:		
mounting position		any
Design of the product		Instantaneous
Supply voltage / for AC / rated value	V	400
Resistance against the impulse current / rated value	kA	1
Ambient temperature	°C	-5 <b>+4</b> 5
Ambient temperature		
during storage	°C	-40 +60
Mechanical operating cycles as operating time / typical		10,000
Overvoltage class		Ш
Supply voltage / for testing equipment / minimum	V	100
Protection against electrical shock		Finger and back-of-hand safe
Position / of power supply cord		top or bottom
Tightening torque		
• with screw-type terminals	N⋅m	2.5 3
Section de conducteur raccordable		
• solid	mm²	1.5 25
• multibrin	mm²	1.5 25
Product feature		

• [not supplied - silicon-free]
• halogen-free

Yes

Number of test cycles / for environmental testing / in accordance with IEC 60068-2-30

Yes

28

## Certificates/approvals:

## **General Product Approval**

**Declaration of Conformity** 



other







**Test Certificates** 

other

Special Test Certificate Type Test
Certificates/Test
Report

Environmental Confirmations

## **Further information:**

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

http://www.siemens.com/lowvoltage/mall

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

http://support.automation.siemens.com/WW/view/en/5SM1342-0/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=5SM1342-0

**CAx-Online-Generator** 

http://www.siemens.com/cax

last change: Dec 31, 2012